

Jolting Volumeter Type STAV II



Range of Application

The apparatus is used for the determination of the apparent volumes before and after settling, the ability to settle as well as the tapped density acc. to the European Pharmacopoeia, DIN ISO 787 Part 11, ISO 3953 and ASTM B 527-93. The possibility of using measuring cylinders of 10, 25, 50, 100, 250, 500 und 1000 ml opens a wide range of industrial applications for this kind of equipment. Investigation of powdery, fibrous and granular products can be performed.

Construction

The distinguishing features of the jolting volumeter STAV II in modern soft design are the round shape and the metallic surface. The main parts of the STAV II are a modern silver metallic plastic housing with one-phase AC motor, the jolting mechanism with clamping device for the measuring cylinder and the ON and OFF switch. The control unit with functional display for simplified operation is arranged in the housing. The ergonomic properties are optimal due to the arrangement of the display. In addition, the jolting volumeter offers the advantage of easy cleaning. The weight and graduation of 250 ml measuring cylinders is standardized according to ISO 4788.

Technical Data

- Speed of camshaft: 250 rpm +/- 15 rpm
- single-phase AC motor, single phase and condenser
- 50 Watt
- Weight of measuring cylinder and clamp: 670 g +/- 45 g
- Dropping height of guide punch: 3 mm +/- 0.1 mm
- Noise level acc. to DIN 45 635: about 80 dBA
- Cable with safety plug: 1.5 m long

Net weight: approx. 9 kg
Dimensions: approx. 290 x 330 x 180 mm
(without measuring cylinder)

Typ	Artikelnummer
STAV II Standard execution 230V, 50 Hz*	05 99 2000 0001
Measuring cylinder	125 99 0008
Noise damping hood	125 75 0001

*Special frequency on request.

Noise Damping Hood

Range of Application

By using the noise damping hood you can reduce the noise level of your jolting Volumeter.
Noise level without hood about 80 dB(A)
Noise level with closed hood about 58 dB(A)
Due to its decorative design the hood fits into any laboratory.

Construction

Housing of wood-plastic-compound, pressed under high pressure, very stable.
Hood in the form of a front pane of plexi glass, transparent, counter and measuring cylinder can be watched when the hood is closed.
The front pane can be arrested in any desired position due to a memory hinge.
The noise-damping lining of Sonex foam material ensures the best possible noise absorption.
An extra thick bottom plate is coated with sound absorbing material preventing the resonance effect.

Net weight: approx. 17 kg
Inside dimensions: approx. 400 x 430 x 550 mm
Outside dimensions: approx. 435 x 450 x 570 mm

Agence Nord:

ZA Object'Ifs Sud - Lot A3
6 Allée Emilie du Châtelet
14123 Ifs
tél : 02.31.34.50.74
fax : 02.31.34.55.17

Agence Est:

Parc Club des Tanneries
2 Rue de la Faisanderie
67380 Lingolsheim
tél : 03.88.04.01.81
fax : 03.68.93.01.52



Agence Sud:

Bât Le Venango. 392 Rue Jean Dausset
AGROPARC - BP11575
84916 Avignon Cédex 9
tél : 04.90.27.17.95 fax : 04.90.27.17.52

www.deltalabo.fr
info@deltalabo.fr