

Low Temperature Grease Flow Tester

test method

This test method is used to assess the flow ability of grease in cold environments. Low temperature flow properties are important grease parameters when it comes to central lubrication systems, vehicles and machineries in harsh environments.

low temperature flow tester

The Low Temperature Flow Tester, K95300, has been developed for testing lubricating greases in low temperature environments. The test is performed in accordance with DIN 51805 and can also be customized.

Low Temperature Flow is measured according to the method of Kesternich (DIN 51805). The K95300 test system is an instrument for the determination of the flow pressure of lubricating grease at temperatures down to -50°C. Due to the special design of the cooling system, the K95300 can cool down in high speed and reach temperatures of -50°C without an expensive external cooling device.

The core components are in accordance with medical standards to ensure highest precision and accuracy even in very low-pressure ranges. An easy to use touch screen interface helps to operate and use the machine in a quick and professional way.

Measurement Principle

A layer of the grease to be tested is put on a glass plate without air bubbles. The measuring nozzle is simply pressed a few times onto the layer of lubrication grease until it is filled with grease. The nozzle is inserted into the thermostatically controlled metal block of the tester and the chamber is air sealed and thermally isolated to ensure best performance.

After the preparation time, the pressure above the sample nozzle is increased in steps until a sudden pressure decrease is observed, indicating that the grease is pressed through the nozzle. The test is stopped and the last pressure value is displayed as the flow pressure according to Kesternich.

The grease removal container is installed under the tester and is easy to clean and replace.

ordering information

catalog no.	description
K95300	Low Temperature Grease Flow Tester 110-230V, 50/60Hz

Agence Nord:
ZA Object'ifs Sud - Lot A3
6 Allée Emilie du Châtelet
14123 Ifs
tél : 02.31.34.50.74
fax : 02.31.34.55.17



Agence Sud:
Bât Le Venango, 392 Rue Jean Dausset
AGROPARC - BP11575
84916 Avignon Cédex 9
tél : 04.90.27.17.95 fax : 04.90.27.17.52

Agence Est:
Parc Club des Tanneries
2 Rue de la Faisanderie
67380 Lingolsheim
tél : 03.88.04.01.81
fax : 03.68.93.01.52

www.deltalabo.fr
info@deltalabo.fr



K95300 Low Temperature
Grease Flow Tester

specifications

Conforms to the specifications of: DIN 51805

Pressure Range: 0 to 3.000 mBar

Pressure Resolution: <1 mBar

Temperature Range: ambient to -50°C

Temperature Resolution: <1°C

PLC: Touch PLC

Internal Generated Air Pressure

Interface: Ethernet

Voltage: 110 – 230V / 50 – 60Hz

Power: 350 W Max.

Software

A touch screen with integrated PLC controls the system and allows easy adjustment of test parameters and quick setups.

Below are some of the key functions:

- Pre-defined pressure settings according to DIN 51805, customized setup possible
- Pre-defined selection of most used temperatures or free selection possible
- Pre-defined increase time of 30 s or custom
- User selectable starting pressure
- Help function directly embedded in the HMI
- Remote monitoring / control via app.

Included Accessories

Basic Machine

Multi Range Power Supply

PLC and HMI Software

1 Testing Sleeve

3 Unloading Containers

Tooling Set

Documentation

Dimensions h x w x d mm (in)

230 x 320 x 440 mm (9 x 12.6 x 17.3 in)

Weight: 25 kg (55 lb)