



A-3 and A-18 Sieves

Two sieve shakers for top results



dry and wet sieving of up to 2 kg on your benchtop

effectively sieve bulk quantities up to 15 kg

three-dimensional sieve motion for extra quick results quality management testing according to DIN EN ISO 9001

20 μm – 125 mm measuring range for separation and fractionation

ideal for pilot production runs or series testing

automatic program selection and amplitude control

Setting the standard in sieving

FRITSCH A-3 – optimum sieving with digital analysis

FRITSCH A-3 and A-3 pro vibrating sieve shakers are just what you need if you regularly perform dry or wet sieving or measure the quantitative particle size distribution of solids and suspensions. You can also use them to separate and fractionate up to 2 kg of material within a size range of 20 μ m to 63 mm. ISO and ASTM test sieves are available in diameters of 100 mm, 200 mm, or 8". The FRITSCH A-3 pro model can also be integrated into any DIN EN ISO 9001 compliant quality management testing system.



As our top model, A-3 pro is your quality control solution for incoming and outgoing goods. Very easy to operate, it is quiet, robust, and durable.

FRITSCH A-18 – the high-capacity sieve shaker for analytical work

The A-18 model lets you effortlessly sieve up to 15 kg of 20 μ m to 125 mm material in a single step. Thanks to its three-dimensional sieving motion, you can achieve particularly fast sieving results with optimum reproducibility and without the need to re-sieve manually. This makes it perfect for pilot production runs or for series testing larger quantities.



We recommend the A-18 Heavy Duty Analytical Sieve Shaker for particle size analysis and the fractionation of coarse-grained material.

Technical data

A-3 pro / A-3 Vibrating Sieves

Measuring range

dry 20 μm – 63 mm* wet 20 μm – 10 mm*

Max. sample quantity dry up to 2 kg* wet up to 100 g*

Connection values

100-240 V/1~ 50-60 Hz, 50 watts

WeightDimensions W x D x H21 kgTable-top unit 37 x 40 x 20 cm

A-18 Heavy Duty Analytical Sieve Shaker

Measuring range

dry 20 μm – 125 mm* wet 20 μm – 10 mm*

Max. sample quantity

dry up to 15 kg* wet up to 1 kg* Electrical demand/output

230 V/1~, 50 – 60 Hz, watts or

115 V/1~, 50–60 Hz, 200 watts

WeightDimensions W x D x H135 kgFloor unit 58 x 59 x 130 cm

* depending on feed material and sieve insert



LTA LABO

Contact us now

14123 lfs

tél : 02.31.34.50.74

fax : 02.31.34.55.17

AGROPARC - BP11575

84916 Avignon Cédex 9

Bât Le Venango. 392 Rue Jean Dausset

tél : 04.90.27.17.95 fax : 04.90.27.17.52

Agence Sud:

Agence Est: Parc Club des Tanneries 2 Rue de la Faisanderie 67380 Lingolsheim tél : 03.88.04.01.81 fax : 03.68.93.01.52

> www.deltalabo.fr info@deltalabo.fr